



1 ELEVATION VIEW
NOT TO SCALE

- GENERAL NOTES:
- (1) DRAWING IS CONCEPTUAL IN NATURE AND IS NOT TO BE USED FOR CONSTRUCTION PURPOSES.
 - (2) SITE INFORMATION IS GENERIC TO ILLUSTRATE GENERALIZED CONDITIONS.
 - (3) LOW CHORD TO BE A MINIMUM OF 12 INCHES CLEAR OF 100-YEAR FLOOD ELEVATION, REQUIRED.
 - (4) GRADING & RIP-RAP DESIGN & INSTALLATION BY OTHERS. NO STEEPER THAN 2:1 GRADING WITH AT LEAST 6" CLEAR OF THE BOTTOM OF PILE CAP IS PREFERRED. RIP-RAP IS RECOMMENDED FOR AREAS WHERE THE POTENTIAL FOR EROSION EXISTS.
 - (5) MINIMUM OF 5' OFFSET FROM EASEMENTS, FLOW EXTENTS, ENVIRONMENTAL BUFFERS, OR SIMILAR RECOMMENDED, UNLESS OTHERWISE ALLOWED AS CONFIRMED BY AHJ.
 - (6) CONSTRUCTION FROM GROUND OR FROM DECK CAN INFLUENCE DESIGN CONSIDERATIONS AND SHOULD BE NOTED IN DESIGN INTENT PER PROJECT.
 - (7) 42" PEDESTRIAN HANDRAIL DESIGNED TO MEET 4" SPHERE RULE.
 - (8) BRIDGE SLOPE NOT TO EXCEED 4.5% FOR A CONTINUOUS PATH OR 7.5% IN AN ADA RAMP & LANDING CONFIGURATION.
 - (9) IMAGERY REPRESENTS A VARIETY OF EXISTING WORK, ALL PROJECTS ARE CUSTOM DESIGNED PER SITE, CLIENT, AND DESIGN INTENT.
 - (10) YORK TIMBER PROTECTIVE SYSTEMS ARE NOT STANDARD BUT RECOMMENDED DECK, RAIL, AND FOUNDATION COATING SELECTIONS THAT ARE CUSTOM TO THE BRIDGE USE, LOCATION, AND DESIGN INTENT FOR INCREASED LONGEVITY.



2 MULTIPLE LONG SPAN BRIDGE PREVIOUS WORK IMAGES
NOT TO SCALE

<p>The Premier Timber Bridge Company</p>	TIMBER PEDESTRIAN BRIDGE	CONCEPT ELEVATION		
	<p>TYPICAL MULTIPLE LONG SPAN CROSSING</p> <p>GENERIC DESIGNED ENVIRONMENT</p>	<p>DESIGNED LOADING</p> <p>90 PSF LOADING (L/360 DEFLECTION)</p>		
<p>These plans are property of York Bridge Concepts. They are not to be reproduced or used without written permission from York Bridge Concepts.</p> <p>2420 brunello trace lutz, fl 33558</p> <p>t: 800.226.4178 f: 800.836.1274</p>	DATE/TIME:	DRAWN BY:	PROJECT NUMBER:	SHEET NUMBER:
	YEAR - 2020	XXXX	###-###	201