



- GENERAL NOTES:
- (1) DRAWING IS CONCEPTUAL IN NATURE AND IS NOT TO BE USED FOR CONSTRUCTION PURPOSES.
 - (2) SITE INFORMATION IS GENERIC TO ILLUSTRATE GENERALIZED CONDITIONS.
 - (3) LOW CHORD TO BE A MINIMUM OF 12 INCHES CLEAR OF 100-YEAR FLOOD ELEVATION, REQUIRED.
 - (4) GRADING & RIP-RAP DESIGN & INSTALLATION BY OTHERS. NO STEEPER THAN 2:1 GRADING WITH AT LEAST 6" CLEAR OF THE BOTTOM OF PILE CAP IS PREFERRED. RIP-RAP IS RECOMMENDED FOR AREAS WHERE THE POTENTIAL FOR EROSION EXISTS.
 - (5) MINIMUM OF 5' OFFSET FROM EASEMENTS, FLOW EXTENTS, ENVIRONMENTAL BUFFERS, OR SIMILAR RECOMMENDED, UNLESS OTHERWISE ALLOWED AS CONFIRMED BY AHJ.
 - (6) CONSTRUCTION FROM GROUND OR FROM DECK CAN INFLUENCE DESIGN CONSIDERATIONS AND SHOULD BE NOTED IN DESIGN INTENT PER PROJECT.
 - (7) 42" PEDESTRIAN HANDRAIL DESIGNED TO MEET 4" SPHERE RULE.
 - (8) 34" VEHICULAR GUIDERAIL & CURBING SYSTEM RATED FOR 10,000 LB CAPACITY.
 - (9) BRIDGE SLOPE NOT TO EXCEED 4.5% FOR A CONTINUOUS PATH OR 7.5% IN AN ADA RAMP & LANDING CONFIGURATION.
 - (10) IMAGERY REPRESENTS A VARIETY OF EXISTING WORK, ALL PROJECTS ARE CUSTOM DESIGNED PER SITE, CLIENT, AND DESIGN INTENT.
 - (11) YORK TIMBER PROTECTIVE SYSTEMS ARE NOT STANDARD BUT RECOMMENDED DECK, RAIL, AND FOUNDATION COATING SELECTIONS THAT ARE CUSTOM TO THE BRIDGE USE, LOCATION, AND DESIGN INTENT FOR INCREASED LONGEVITY.

1 ELEVATION VIEW
NOT TO SCALE



2 MULTIPLE SPAN BRIDGE PREVIOUS WORK IMAGES
NOT TO SCALE

YORK
BRIDGE CONCEPTS
The Premier Timber Bridge Company

These plans are property of York Bridge Concepts. They are not to be reproduced or used without written permission from York Bridge Concepts.
2420 brunello trace t: 800.226.4178
lutz, fl 33558 f: 800.836.1274

TIMBER VEHICULAR BRIDGE

TYPICAL MULTIPLE SPAN CROSSING
GENERIC DESIGNED ENVIRONMENT

CONCEPT
ELEVATION

DESIGNED LOADING
VEHICULAR: HS20-44 (L/400 DEFLECTION)
PEDESTRIAN: 90 PSF LOADING (L/360 DEFLECTION)

DATE/TIME: YEAR - 2020	DRAWN BY: XXXX	PROJECT NUMBER: ###-###	SHEET NUMBER: 201
---------------------------	-------------------	----------------------------	----------------------